

Our office is closed on Monday April 29th & Tuesday April 30th for Passover



Home > Products > ProX Truss > Couplers, Spacers, and Hardware > Spacers > 0.68ft (0.210m) Square Truss Segment

SKU: XT-SQ068

Permalink:

[Search on Google](#)

0.68ft (0.210m) Square Truss Segment

[Find A Dealer](#)

Product Images



[Download Product Images](#)

Our Products And You

[Submit your story](#)

ProX XT-SQ068 0.68ft (0.210m) Square Truss Segment

Description

ProX XT-SQ068 Truss Segment is one of the most trusted staging support systems in the live entertainment industry and is engineered and manufactured to the highest standards of safety and performance. We manufacture with [EN-AWT6 6082 Aluminum](#) for safety and strength. Our XT series F34 square truss utilizes a popular conical connector system, which easily mates with most other brands of the truss of the same size and connector type, and is available in a variety of lengths to suit your designs. Our outstanding quality control and manufacturing techniques assure excellent fitment at every connection to expedite your setups.

ProX XT-SQ series trussing is a rugged and durable trussing solution perfect for live outdoor or indoor productions, exhibitions, retail displays as well as nightclubs, and other permanent installations. ProX offers a wide variety of corners, base plates, connectors, and accessories that allow limitless design configurations to suit your needs. *Always consult an engineer for complex designs!*

ProX XT-SQ SERIES DIMENSIONS:

- Height: 11.42in / 290mm
- Width: 11.42in / 290mm
- Weight: 21lb/9,5kg per 3.28 ft / 1 meter
- Main Tube: 2in / 50mm
- Wall Thickness: .08in / 2mm
- Braces: .75in / 20mm

IMPORTANT: Always know your load weight for your equipment: [XT-SQ Truss Loading Chart](#)

Features

- **Manufactured to Exacting Specifications in our Own Factory!**
- **Actual Height: 0.68 ft (0.25 Meter) Square Truss Segment**
- **Actual Weight: 6 Lbs.**
- **Includes One Connecting Hardware Set**
- **Material: EN-AWT6 6082 Aluminum**
- **TUV Certified Aluminium Welding**





TUV is a 3rd Party Certification Body and a Nationally Recognized Testing Laboratory (NRTL). TUV provides inspections, testing, certification & training, with the ultimate objectives of reliability, safety & high quality.

ProX Truss products utilize industry standard dimensions to be compatible to connect to/ and work with many other manufacturers of F34 trussing products with conical connectors.

Exterior Dimensions & Weight

8.25"H x 11.75"W x 11.75"L - Weight: 9.00 lbs

Shipping Dimensions & Weight

Box 1 of 1: 9.50"H x 12.50"W x 12.50"L - Shipping Weight: 10.00 lbs

UPC

804589616238

Our Products and You

Submit your story

Commonly Asked Questions

+ Where can I buy one?

[submit a question](#)

Customer Testimonials


What did you think

Related Products



Spacer 105mm Female Coupler

SKU: XT-SPFF105



Spacer 170mm (6.69") female

Spacer 170mm Female Coupler

SKU: XT-SPFF170



Spacer 210mm (8.27") female

Spacer 210mm Female Coupler

SKU: XT-SPFF210



0.82ft 0.25m Square Truss Segment

SKU: XT-SQ082

