



Home > Products > ProX Stands > Lighting Truss & Crankstands > 10-Foot Height Adjustable Portable Crank Lighting Stand System with included 2x T-Bars Triangle Truss for 5ft 10ft 15ft Width

SKU: T-LS35C

Permalink: <http://www.proxdir.com>

[Search on Google](#)

## 10-Foot Height Adjustable Portable Crank Lighting Stand System with included 2x T-Bars Triangle Truss for 5ft 10ft 15ft Width

[Find A Dealer](#)

### Product Images



[Download Product Images](#)

### Our Products And You



[submit your story](#)

### ProX T-LS35C 10-Foot Height Adjustable Portable Crank Lighting Stand System with included 2x T-Bars Triangle Truss for 5ft 10ft 15ft Width

#### Description

ProX T-LS35C 10-Foot Height **Adjustable Portable Crank Lighting Stand System with included 2x T-Bars Triangle Truss for 5ft 10ft 15ft Width**. Introducing the ProX T-LS35C, a versatile triangular crank truss system designed to meet your lighting needs. This package includes two robust crank-up stands and three 5-foot triangle truss sections, providing you with the flexibility to create spans ranging from 5 - 15 feet.

With a safe height range of 9-10 feet, this medium-duty truss stand ensures stability for your lighting setup. Included in the package are a pair of T-Adapters for hassle-free truss mounting, allowing you to securely **attach up to 360 lbs of equipment evenly**. The truss tubes boast a 35mm (1-3/8-inch) diameter, while the truss sections measure 6 inches in overall width and 57 inches in length.

For added convenience, consider complementing your T-LS35C truss crank system with our high-quality carry bags. Crafted with precision and using top-notch materials, these bags are designed to transport your truss system safely and securely. The optional carry bag, T-LS35C-BAG, is available separately, ensuring that you can easily transport your equipment and keep it in prime condition wherever your events take you. Elevate your lighting game with the ProX T-LS35C and experience reliable, professional-grade truss solutions that cater to your performance needs.

#### Ships in (2) separate boxes:

**Box 1 of 1:** 3x Truss Sections: 57.5"x24"x11" - **Weight:** 43 lbs

**Box 2 of 2:** 2x Crank stands 59"x16"x10" - **Weight:** 55 lbs

**Product Weight:** 92 Lbs

**Basic Usage:** Ensure that the stand is positioned on a hard stable surface, in a suitable location, on firm ground, and clear of overhead obstacles. Stabilize legs before lifting the tower or any load. When outdoors, secure the tower with braces or cables, in case of wind. Check the cable, it should not show damaged or flattened areas or broken strands.

**Using the Winch:** For Lifting the tower, turn the winch handle clockwise.  
To lower the tower, turn the winch handle counter-clockwise.

#### Safety Notes:

Loading on trusses and stands should comply with rated weights.  
Lock all the safety mechanisms (safety pins, knobs)  
Loads must be centered & balanced on each lifting unit.  
Safety chains must be installed on each item attached to the unit.  
Leave a safety perimeter with a radius 5ft greater than the maximum height of the stands during lifting and lowering of loads.  
During transport, close all the sections and lock the lifting carriage.  
Do not attempt to move the stand when loaded or in the extended position.

**Service Notes:** Servicing and repairs must be made by qualified persons.  
Cable, pulleys, and telescopic masts must be inspected before each use. Any damaged cable must be replaced immediately.  
An annual inspection by an authorized technician is suggested.

Exercise caution when loading this or any ProX truss system. Be sure to evenly distribute your fixtures or equipment for safety. Always use a safety cable or chain on all mounted fixtures.

#### Safety Instructions:

To avoid problems a competent person should inspect all rigging hardware, stands, and equipment before each use and periodically do a major inspection for signs of wear, abuse, and general adequacy, as well as perform any manufacturer-recommended preventive maintenance on schedule. Observe all warnings and usage instructions in the full manual.

---

#### Features

- **Sections Range from 5 Ft to 14 Ft. (57" per section)**
- **Equipped with 5 Ft, 10 Ft, or 15 Ft. width configurations**
- **Complete portable multi-size lighting truss system**
- **Package includes (2) 10-foot Cranking System Stands + (2) T-Bars**
- **Max Load: Supports up to 360 lbs (evenly distributed)**
- **Tubing: 1.5-inch diameter**

---

#### Package Contents

- [T-LS35C-STAND](#) (1) Set of (2) 9.5 Ft Crank Stands with T-Bars Supports Triangle Truss Segments for DJ Lighting
- [T-LS35C-TRUSS](#) (1) ProX Set of (3) Universal Lighting Truss System with 5Ft 10Ft 15Ft Triangle Segment Sections

---

#### Exterior Dimensions & Weight

Weight: 33.00 lbs

#### Shipping Dimensions & Weight

**Box 1 of 2:** 3x Truss Sections 9.00"H x 20.00"W x 57.00"L - Shipping Weight: 33.00 lbs

**Box 2 of 2:** 2x Crank stands 10.00"H x 59.00"W x 16.00"L - Shipping Weight: 55.00 lbs

#### Suggested Shipping Method: Parcel

#### UPC

741459148232

---

#### Our Products and You

Submit your  
story

---

#### Commonly Asked Questions

+ Where can I buy one?

[submit a question](#)

---

#### Customer Testimonials

What did you think

---

#### Related Products



**[10ft Medium Duty Lighting Crank Stand](#)**  
SKU: XT-LS01C



---

**10' Ft. High Performance Dual 1/4" TS Male to Dual XLR Male Unbalanced Audio Cable**  
SKU: XC-DPXM10



---

**Fusion RGBWA Par 36x 1W LED Slim Par White Housing**  
SKU: X-PAR36RGBWA1WWIRC



---

**Plastic O Style Clamp for 2" (50mm) and 1.5" (38mm) Truss Tube Capacity 28 Lbs.**  
SKU: T-C3

