Find A Dealer



Home > Products > ProX Truss > Roofing Systems > Stage Roofing Packages > 12D PR2 Stage Roofing System with 7 Ft Speaker Wings and 6 Chain Hoists | 30 Ft W x 20 Ft L x 23 Ft H

SKU: XTP-GS302023-PR2-12D

Permalink: http://www.proxdire

Search on Google

12D PR2 Stage Roofing System with 7 Ft Speaker Wings and 6 Chain Hoists | 30 Ft W x 20 Ft L x 23 Ft H

Product Images



Our Products And You



ProX XTP-GS302023-PR2-12D 12D PR2 Stage Roofing System with 7 Ft Speaker Wings and 6 Chain Hoists | 30 Ft W x 20 Ft L x 23 Ft H

Description

The **ProX XTP-GS302023-PR2-12D Stage Roofing System with Speaker Wings**is 30'W x 20'L x 23'H and Includes 6 Chain Hoists. The 30-foot by 20-foot trussing area is large enough to cover a multi-person live band or a very large DJ production set up and the 7 foot wings are more than enough to hang speakers and lighting fixtures. You can hang lighting, curtains, video screens and speakers from the truss system and adjust the height up to 23 feet high. Scalable to smaller staging needs. The entire structure is lifted and held in place with Six (6) chain hoist lifting stations that are the stands that support the entire system. The stage roof trussing is designed to hold lighting and audio gear evenly distributed around the stage roofing system. **Guy wires required for most installations!**

In this package, you have everything you need for a complete roofing solution:

- 6 XTP-GSBPACK3 Truss Tower Lift Systems,
- 16 XT-SQ984 9.84ft (3.00m) Square Truss Segment,
- 8 XT-SQ715 7.15ft(2.15m) Square Truss Segment,
- 8 XT-SQ12D 9"(0.23m) 12D Corner,
- 2 XT-SQ656 6.56ft(2.00m) Square Truss Segment,
- 3 XT-MCH1TX2-30FT Sets of 2 1T Manual Chain Stage Hoist with 30ft Chain,

ProX XT-SQ series trussing is a rugged and durable trussing package solution. Perfect for live outdoor or indoor productions, exhibitions, as well as nightclubs, and other permanent installations. **ProX Live Performance Gear®** offers a wide variety of single tubes, mounting plates, clamps and accessories that allow limitless design configurations to suit your needs. Always consult an engineer for complex designs!

ProX XT-SQF34 2MM SERIES DIMENSIONS:

- Height: 11.42in / 290mmWidth: 11.42in / 290mm
- Weight: 21lb/9,5kg per 3.28 ft / 1 meter
- Main Tube: 2in / 50mmWall Thickness: .08in / 2mmBraces: .75in / 20mm

IMPORTANT: Always know your load weight for your equipment: XT-SQ Truss Loading Chart

- Manufactured to Exacting Specifications in our Own Factory!
- Tolerance Free Standard Conical Connectors
- · Truss Main Tube Wall Thickness of .08in / 2mm
- . Load Capacity is 1 Ton (2000 lbs) per corner lift unit (4 tons total weight including truss)
- Material: EN-AWT6 6082 Aluminum and Welded Steel (Painted Black)
- TUV Certified Aluminium/Steel Welding

TUV is a 3rd Party Certification Body and a Nationally Recognized Testing Laboratory (NRTL). TUV provides inspections, testing, certification & training, with the ultimate objectives of reliability, safety & high quality.

ProX Truss products utilize industry standard dimensions to be compatible to connect to/ and work with many other manufacturers' F34 trussing products with conical connectors.

Package Contents

- XT-SQ984 (16) 9.84 Ft 3.00 M F34 Square Truss Segment | 2 mm Wall
- XT-SQ705 (8) 7.05 Ft 84.64 Inch 2.15 M F34 Square Truss Segment 2 mm Wall
- XT-SQ12D (8) 12 Degree F34 Square Truss Angle Connector | 2mm Wall
- XT-SQ656 (2) 6.56 Ft 2.00 M F34 Square Truss Segment | 2 mm Wall
- XT-MCH1TX2-30FT (3) Pair 1 Ton Manual Chain Hoist with 30 Ft (9 M) Chain for Stage Truss roof system and line array speakers
- XT-BLOCK-MK2 (6) Ground Support Sleeve Block for F34 Truss Segment Systems
- XT-TOPCM (6) Top Truss Section for Electric Motor or Manual Chain Hoist
- XT-GSB MK3 (6) Universal Vertical Tower Truss Ground Support Base on Wheels with Leveling Jacks for F34, F44 and 12" Bolt truss
- XT-SQ328 (6) 3.28 Ft 1.00 M F34 Square Truss Segment | 2 mm Wall
- XT-HINGE (24) Conical Tube Ground Support Post towers Male to Male Hinge Joint Fits F31 F32 F34
- XT-GSOUTS3 (24) Single 3 Ft. Outrigger Support Brace for Leveling Ground Support Truss Tower Base

Exterior Dimensions & Weight

XT-GSOUTS3 (24): 64.00"H x 2.00"W x 37.50"L - Weight: 29.00 lbs XT-SQ328 (6): 39.36"H x 11.42"W x 11.42"L - Weight: 19.00 lbs XT-TOPCM (6): 11.50"H x 9.50"W x 24.00"L - Weight: 26.40 lbs XT-BLOCK-MK2 (6): 18.50"H x 22.50"W x 22.50"L - Weight: 77.30 lbs XT-SQ656 (2): 78.72"H x 11.42"W x 11.42"L - Weight: 31.00 lbs XT-SQ12D (8): 11.42"H x 11.42"W x 10.00"L - Weight: 8.00 lbs XT-SQ984 (16): 118.08"H x 12.00"W x 12.00"L - Weight: 42.00 lbs

Shipping Dimensions & Weight

Box 1 of 11: XT-GSOUTS3 (24 boxes) 6.00"H x 8.00"W x 64.00"L - Shipping Weight: 34.00 lbs
Box 2 of 11: XT-HINGE (24 boxes) 2.00"H x 5.00"W x 5.00"L - Shipping Weight: 2.50 lbs
Box 3 of 11: XT-SQ328 (6 boxes) 41.50"H x 12.50"W x 12.50"L - Shipping Weight: 21.00 lbs
Box 4 of 11: XT-GSB MK3 (6 boxes) 9.00"H x 29.00"W x 29.00"L - Shipping Weight: 70.00 lbs
Box 5 of 11: XT-TOPCM (6 boxes) 12.00"H x 10.00"W x 25.00"L - Shipping Weight: 28.00 lbs
Box 6 of 11: XT-BLOCK-MK2 (6 boxes) 20.00"H x 24.00"W x 24.00"L - Shipping Weight: 80.00 lbs
Box 7 of 11: XT-MCH1TX2-30FT (3 boxes) 11.00"H x 19.00"W x 15.00"L - Shipping Weight: 104.00 lbs
Box 8 of 11: XT-SQ656 (2 boxes) 80.50"H x 13.00"W x 13.00"L - Shipping Weight: 35.00 lbs
Box 9 of 11: XT-SQ12D (8 boxes) 12.00"H x 12.00"W x 12.00"L - Shipping Weight: 9.00 lbs
Box 10 of 11: XT-SQ705 (8 boxes) 13.00"H x 13.00"W x 86.00"L - Shipping Weight: 30.00 lbs
Box 11 of 11: XT-SQ984 (16 boxes) 14.00"H x 14.00"W x 12.00"L - Shipping Weight: 46.00 lbs

Suggested Shipping Method: LTL

UPC

804589617570

Our Products and You

Submit your story

Commonly Asked Questions

Customer Testimonials

What did you think