



Home > Products > ProX Truss > Pre-Rigging & Mobile Systems > , Mounting Accessories > 24" Truss Tube with Dual Clamp for ProX XT-GRU Rapid Grid Modular System

SKU: XT-GRU-ARM

Permalink: <http://www.proxdir.com>

[Search on Google](#)

24" Truss Tube with Dual Clamp for ProX XT-GRU Rapid Grid Modular System

[Find A Dealer](#)

Product Images



[Download Product Images](#)

Our Products And You

Submit your story

ProX XT-GRU-ARM 24" Truss Tube with Dual Clamp for ProX XT-GRU Rapid Grid Modular System

Description

ProX XT-GRU-ARM 24" Truss Tube with Dual Clamp for ProX XT-GRU Rapid Grid Modular System 3mm 19.5" pole (24" Total) with Pro Clamp instantly gives you a sturdy mounting surface for any clampable professional Truss Rigger to Mobile DJ for an array of lighting or other types fixtures. Made from high-grade aluminum the XT-GRU-ARM is lightweight yet sturdy enough to handle almost any mountable device. It fits any standard 2" trussing and is an easy and affordable addition to easily expand your current DJ or Professional Stage Trussing Rig.

The XT-GRU3024 Rapid Grid™ modular design allows endless configurations for single fixtures, double hanging or ladders of multiple fixtures, which can also be expanded to create a wall of hanging positions. Each U module has two safety point attachments, one on each side for use with multiple styles of fixtures. The ProX GRU Rapid Grid™ System has been designed for quick deployment and take down in any environment. The lightweight yet strong aluminum construction is additionally reinforced to provide added stability and safety.



TUV Is a 3rd Party Certification Body and a Nationally Recognized Testing Laboratory (NRTL). TUV provides inspections, testing, certification & training, with the ultimate objectives of reliability, safety & high quality.

Features

- 19.5" Width (24" with Clamps)
- 2" Diameter Pole
- Dual **T-C4S** Clamp Design
- Connects to 2" Diameter F34 Truss
- Aluminum Pro Dual Clamp For 2" (50mm) Tubing
- Minimum Tubing Diameter 1.9" (48mm)
- Maximum Tubing Diameter 2.008" (51mm)
- Max Load Per Side Capacity 660lbs (300 kgs)
- Compatible with Most Brands
- M10 Bolts

- TUV Approved

Shipping Dimensions & Weight

Box 1 of 1: 3.00"H x 24.00"W x 5.00"L - Shipping Weight: 4.00 lbs

Suggested Shipping Method: Parcel

UPC

019372413820

Master Box

QTY 2 pcs

6.00"H x 25.00"W x 6.00"L

Shipping Weight: 8.00 lbs

Number of Master Boxes: 1

Our Products and You

Submit your
story

Commonly Asked Questions

+ Where can I buy one?

[submit a question](#)

Customer Testimonials

What did you think

Related Products




[30 x 24 in. U Shape Module for ProX XT-GRU Rapid Grid Modular System](#)

SKU: XT-GRU3024



[24" Width Module Top Bar for ProX XT-GRU Rapid Grid Modular System](#)

SKU: XT-GRTOP24



[24 x 30 in. Module Base Plate with Locking Casters for ProX XT-GRU Rapid Grid Modular System](#)

SKU: XT-BP2430W
