

Our office is closed on Monday April 29th & Tuesday April 30th for Passover



Home > Products > ProX Truss > BoltX™ 12" Black Segments 3mm > BoltX™ Segments Black > 3 Ft. BoltX Black Bolted 12 Inch Professional Box Truss Segment | 3mm Wall – Black Finish

SKU: XT-BT1203 BLK

Permalink:

[Search on Google](#)

3 Ft. BoltX Black Bolted 12 Inch Professional Box Truss Segment | 3mm Wall – Black Finish

[Find A Dealer](#)

Product Images



[Download Product Images](#)

Our Products And You

Submit your story

XT-BT1203 BLK 3 Ft. BoltX Black Bolted 12 Inch Professional Box Truss Segment | 3mm Wall – Black Finish

Description

ProX XT-BT1203 BLK BoltX™ Professional Box Truss is designed and engineered for many applications like stage lighting, concerts, Ninja Obstacle Course type construction, and similar uses. Setting ourselves apart from other box truss manufacturers BoltX™ has an innovative end plate designed and manufactured with heavy-duty aluminum material, welded on both sides, and our exclusive circular rings at each corner of the truss to reduce or eliminate damage to the main chord ends. Since box trussing is often dropped or is dragged along concrete floors, this design will substantially lessen the need for expensive repairs to the tubes from mishandling of the truss sections. Our outstanding quality control and manufacturing techniques assure excellent fitment at every connection to expedite your setups.

Compatible with most other 12" Professional Box Truss Manufacturers utilizing a 6.75" bolt center pattern.

Each section of the truss includes one set of Four 5/8" - 11 x 2.5" (NC) attachment bolts, nuts, flat & lock washers.

IMPORTANT NOTE: All bolts in a span of truss must face the same direction, and truss uprights need to have the bolts on top, nuts on the bottom. When you are tightening the bolts, always wrench down with your ratchet from the nut side, and only turn a few cranks past firm. Bolts should be inspected on a regular basis. Washers must be used on both sides of a connection. Bolt sets should be replaced periodically as normal use degrades the threads on both the bolt and the nut. If you over-tighten your bolts you risk seriously damaging or even breaking them. Remember that any time you are bolting the truss, safety is of the highest importance. This is not a subject to be taken lightly. Before raising a bolted box truss build, one person should inspect all truss connections and the rigging.

IMPORTANT: Always know your load weight for your equipment. [Download Loading Chart](#)

Features

ProX Live Performance Gear® recommends that you engage the services of a licensed engineering professional for complex loading configurations and/or conditions.

- 12" H x 12" W Professional Box Truss W/Bolt Connection.
- Industry Standard Bolt Pattern 6 3/4" x 6 3/4" with 5/8" Holes
- Load Tested & Inspected During Manufacturing and Quality Control
- Includes one set of Four 5/8" - 11 x 2.5" (NC) attachment bolts, nuts, flat & lock washers.
- Compatible with most other 12" Professional Box Truss Manufacturers
- Outer Tube Diameter of 2", Wall Thickness 3mm (1/8"), Diagonal 1", Wall of 3mm (1/8"),
- Welded to TÜV standards, 6082-T6 Alloy by GSI SLV-certified welders
- Finish: Black Coated Aluminum



TÜV is a 3rd Party Certification Body and a Nationally Recognized Testing Laboratory (NRTL). TÜV provides inspections, testing, certification & training, with the ultimate objectives of reliability, safety & high quality.

ProX BoltX™ Truss products utilize industry standard dimensions to be compatible to connect to/ and work with many other manufacturers 12 In. Bolted Box trussing products.

Exterior Dimensions & Weight

12.00"H x 12.00"W x 36.00"L - Weight: 27.00 lbs

Shipping Dimensions & Weight

Box 1 of 1: 13.00"H x 13.00"W x 37.00"L - Shipping Weight: 33.00 lbs

UPC

019372414506

Our Products and You

Submit your
story

Commonly Asked Questions

+ Where can I buy one?

[submit a question](#)

Customer Testimonials

What did you think
