



Home > Products > ProX Cables > DMX > 6" DMX Male 3-Pin to DMX Female 5-Pin Coupler Patch Cable

SKU: XC-DMX3M5F

Permalink:

[Search on Google](#)

## 6" DMX Male 3-Pin to DMX Female 5-Pin Coupler Patch Cable

[Find A Dealer](#)

### Product Images



[Download Product Images](#)

### Our Products And You

[Submit your story](#)

### ProX XC-DMX3M5F 6" DMX Male 3-Pin to DMX Female 5-Pin Coupler Patch Cable

#### Description

The **ProX XC-DMX3M5F** 6" Male XLR-3 to Female XLR-5 DMX Cable Adapter cable is ideal for DMX connection applications where a device with a male XLR-3 DMX output/input needs to be connected to a device with a female XLR5 DMX output/input.

We know cables are not just cables, they are what protects your signal from being altered. Uncompromised signal power, with precise data transmission, is paramount for quality DMX control operations.

Bending & Twisting, are no match for our high-performance tour-grade DMX cables. They're designed to provide years of dependable service and outlast every other cable on the market! Complete Coil technology demands consistent weave tolerances to create precise and accurate data transmission. This is the most important part of the design and greatly affects performance.

#### Technical Specifications

- Polyethylene insulation
- Twisted Pair Data Cable
- Polyethylene inner jacket
- Duofoil® (100% coverage)
- Cotton plus a tinned copper braid shield (85% coverage)
- PVC jacket for durability
- Nominal Characteristic Impedance: 110 Ohms
- Nominal Capacitance Conductor to Conductor @ 1KHz: 12.8 pF/ft
- Nominal Cap Cond. To Other Cond. & Shield @ 1KH z: 23 pF/ft
- Nominal Velocity of Propagation: 66%
- Nominal Delay: 1.6 Nanoseconds per foot
- Nominal Conductor DC Resistance @ 20 degrees C: 24 Ohms/1000 ft
- Nominal Outer Shield DC Resistance @ 20 degrees C: 3.4 Ohms/ 1000 ft
- Nominal Attenuation (dB/100 ft): 0.6 (@ 1 MH z) dB/100 ft
- Maximum Recommended Current: 2.1 Amps per conductor @ 25 degrees C
- Operating Temperature Range: (-30 degrees C To + 75 degrees C)

#### Features

- **ProX Branded, All Metal Connectors**
- **Excellent Durability and Superior Data Transfer**
- **22 AW TC-Tinned Copper Conductor**

- Gold- & Silver-Plated contacts
- Tough Metal / Plastic Chassis
- Flexible PVC Jacket
- Limited Lifetime Warranty

---

#### Shipping Dimensions & Weight

Box 1 of 1: 1.00"H x 1.00"W x 2.00"L - Shipping Weight: 0.20 lbs

Suggested Shipping Method: Parcel

#### UPC

741459146948

---

### Our Products and You

Submit your story

---

### Commonly Asked Questions

+ Where can I buy one?

[submit a question](#)

---

### Customer Testimonials

What did you think

---

### Related Products



#### 6" DMX Male 3-Pin to DMX Female 5-Pin Coupler Patch Cable

SKU: XC-DMX3M5F



#### 6" DMX Male 5-Pin to DMX Female 3-Pin Coupler Patch Cable

SKU: XC-DMX5M3F



#### DMX Male 5-pin Terminator Locking Plug Connector

SKU: XC-DMX5PTR



#### 3 Ft. High Performance DMX Male 3-Pin to DMX Female 3-Pin Coupler Patch Cable

SKU: XC-DMX03



---

**5 Ft. High Performance DMX Male 3-Pin to DMX Female 3-Pin Coupler Patch Cable**

SKU: XC-DMX05

