#### Our office is closed on Monday April 29th & Tuesday April 30th for Passover



Home > Products > ProX Truss > F34 Conical Segments 2mm > Specialty Shapes , Hinges , Mounting Accessories > Adjustable Book-Hinge Connection 0° to 180° for F34 Conical Truss

#### SKU: XT-BOOKHINGE

Permalink: http://www.proxdire

Search on Google

# Adjustable Book-Hinge Connection 0° to 180° for F34 Conical Truss

Find A Dealer

## **Product Images**



#### **Our Products And You**

Submit your storv

### ProX XT-BOOKHINGE Adjustable Book-Hinge Connection 0° to 180° for F34 Conical Truss

### Description

The ProX XT-BOOKHINGE Adjustable Book-Hinge Truss Connection from the most trusted staging support systems in the industry, and is built to the highest standards of safety and performance. It's a rugged yet lightweight trussing solution perfect for mobile DJs, bands, outdoor performances, nightclubs, live mobile productions, or permanent installations. It adjusts from 0° to 180° and fits ProX 12" SQ F34 Conical trussing. Manufactured from high-grade and lightweight aluminum which is easy for transportation and setup! This product can provide a universal solution for truss angles.

The ProX XT-BOOKHINGE is the first trussing hinge from ProX that adjusts from 0° to 180° for unique truss construction projects. There is a built-in adjustable arm to lock the desired angle between sections of truss for unique builds. The superior construction quality of ProX trussing products guarantees many years of trouble-free use.

At the heart of the system is square truss that utilizes a standard conical connector system, which easily mates with other brands of trussing of the same size and connector style, and is available in a variety of lengths to suit your designs. It also works with different types of corners, base plates, connectors and accessories that add stability while expanding on limitless configurations. Always know your load weight for your equipment: VERY IMPORTANT - CLICK HERE for Truss Loading Chart.

# **XT-SQ SERIES DIMENSIONS:**

• Height: 11.42in / 290mm • Width: 11.42in / 290mm

• Weight: 21lb per 3.28 ft / 9,5kg per meter

• Main Tube: 2in / 50mm • Wall Thickness: .08in / 2mm

• Braces: .75in / 20mm

• Tolerance Free Standard Conical Connector

• Main tube wall thickness of .08in

Connecting hardware included - Conical connectors, spigots, cotter pins (8 sets)

ProX Truss products utilize industry standard dimensions to be compatible to connect to/with many other manufacturers trussing.

#### **Features**

- Manufactured in our Own Factory!
- · Allows angles not possible with standard trussing corners
- · Adjustable lock arm
- · Conical couplers included
- Material: 10mm EN-AWT6 6061 Aluminum
- TUV Certified Aluminium Welding



**TUV** Is a 3rd Party Certification Body and a Nationally Recognized Testing Laboratory (NRTL). TUV provides inspections, testing, certification & training, with the ultimate objectives of reliability, safety & high quality.

### **Exterior Dimensions & Weight**

0.00"H x 11.42"W x 11.42"L - Weight: 19.00 lbs

#### **Shipping Dimensions & Weight**

Box 1 of 1: 14.00"H x 14.00"W x 13.00"L - Shipping Weight: 20.00 lbs

Suggested Shipping Method: Parcel

UPC

019372412649

# **Our Products and You**

Submit your story

# **Commonly Asked Questions**

+ Where can I buy one?

submit a question

# **Customer Testimonials**

What did you think