Our office is closed on Monday April 29th & Tuesday April 30th for Passover



Home > Products > ProX Truss > Ground Support > Sleeve Blocks > Ground Support Sleeve Block for F34 Truss Segment Systems Black Finish



Ground Support Sleeve Block for F34 Truss Segment Systems Black Finish

Product Images

Our Products And You

Submit your story

ProX XT-BLOCK-BLK Ground Support Sleeve Block for F34 Truss Systems Black Finish

Description

The **ProX XT-BLOCK BLK** Truss Ground Support Sleeve Block is designed for F34 Series 12" Trussing and it includes 4 connecting sides and is one the most trusted staging support systems in the industry and is built to the highest standards of safety and performance. It's a rugged and durable trussing solution perfect for live outdoor productions, nightclubs, and permanent installations. ProX XT Series Truss compares favorably to the other major trussing manufacturers. We manufacture with EN-AWT6 6082 Aluminum for safety and strength. Our XT series F34 square truss utilizes a standard conical connector system, which easily mates with other brands of the truss of the same size and connector type, and is available in a variety of lengths to suit your designs -- while our outstanding quality control and manufacturing techniques assure excellent fitment at every connection. ProX offers a wide variety of corners, base plates, connectors and accessories that add stability while expanding on limitless design configurations.

Always know your load weight for your equipment: VERY IMPORTANT - CLICK HERE for Truss Loading Chart.

- Tolerance Free Standard Conical connector
- Main tube wall thickness of .08in

XT-SQ SERIES DIMENSIONS:

- Height: 11.42in / 290mm
- Width: 11.42in / 290mm
- Weight: 21lb per 3.28 ft / 9,5kg per meter
- Main Tube: 2in / 50mm
- Wall Thickness: .08in / 2mm
- Braces: .75in / 20mm

Find A Dealer

Features

- Manufactured in our Own Factory!
- Material: EN-AWT6 6082 Aluminum
- TUV Certified Aluminium Welding
- · Built to exacting specifications
- · Includes tapered shear pins with clips



TÜVRheinland TUV Is a 3rd Party Certification Body and a Nationally Recognized Testing Laboratory (NRTL). TUV provides inspections, testing, certification & training, with the ultimate objectives of reliability, safety & high quality.

ProX Truss products utilize industry-standard dimensions to be compatible to connect to/with many other manufacturers F34 trussing products.

Exterior Dimensions & Weight 18.00"H x 23.00"W x 23.00"L - Weight: 74.00 lbs

Shipping Dimensions & Weight

Box 1 of 1: 20.00"H x 24.50"W x 24.50"L - Shipping Weight: 82.00 lbs

Suggested Shipping Method: Parcel

UPC 804589615125

Our Products and You

Submit your story

Commonly Asked Questions

+ Where can I buy one?

submit a question

Customer Testimonials

What did you think

Related Products

Top Truss Section for Electric Motor or Manual Chain Hoist SKU: XT-TOPCM





Universal Vertical Tower Truss Ground Support Base on Wheels with Leveling Jacks for F34, F44 and 12" Bolt truss SKU: XT-GSB MK3





Single 3 Ft. Outrigger Support Brace for Leveling Ground Support Truss Tower Base SKU: XT-GSOUTS3



3.28ft - 1.00m F34 Segment Black Powder Coated | 2mm Wall SKU: XT-SQ328BLK



Pair 1 Ton Manual Chain Hoist with 30 Ft (9 M) Chain for Stage Truss roof system and line array speakers SKU: XT-MCH1TX2-30FT