



Home > Products > ProX Truss > BoltX™ 12" Black Segments 3mm > BoltX™ Accessories Black , Hinges > Center Pivot Hinge Bolted Truss variable corner Articulating Block

SKU: XT-BT12PVT BLK

Permalink: [Search on Google](#)

Center Pivot Hinge Bolted Truss variable corner Articulating Block

[Find A Dealer](#)

Product Images

[Download Product Images](#)

Our Products And You

[Submit your story](#)

ProX Center Pivot Hinge Bolted Truss variable corner Articulating Block

Description

The ProX **XT-BT12PVT BLK** Center Pivot Hinge horizontal variable corner Articulating Block from the most trusted staging support systems in the industry and is built to the highest standards of safety and performance. It's a rugged yet lightweight trussing solution perfect for mobile DJs, bands, outdoor performances, nightclubs, live mobile productions, or permanent installations.

It adjusts from **0° to 180°** and fits ProX 12" **BoltX™** Bolted Truss Segments. Manufactured from high-grade and lightweight aluminum which is easy for transportation and setup! This product can provide a universal solution for truss angles. There is a built-in adjustable arm to lock the desired angle between sections of truss for unique builds. The superior construction quality of ProX trussing products guarantees many years of trouble-free use.

*ProX Truss products utilize industry standard dimensions to be compatible to connect to/with many other manufacturers trussing.

Features

ProX Live Performance Gear® recommends that you engage the services of a licensed engineering professional for complex loading configurations and/or conditions.

- **12" H x 12" W Professional Box Truss W/Bolt Connection.**
- **Industry Standard Bolt Pattern 6 3/4" x 6 3/4" with 5/8" Holes**
- **Load Tested & Inspected During Manufacturing and Quality Control**
- **Includes one set of Four 5/8" - 11 x 2.5" (NC) attachment bolts, nuts, flat & lock washers.**
- **Compatible with most other 12" Professional Box Truss Manufacturers**
- **Outer Tube Diameter of 2", Wall Thickness 3mm (1/8"), Diagonal 1", Wall of 3mm (1/8"),**
- **Welded to TÜV standards, 6082-T6 Alloy by GSI SLV-certified welders**
- **Black Powder Coated Finish**

UPC

804589615347

Our Products and You

[Submit your story](#)

story

Commonly Asked Questions

Ask a question

Customer Testimonials

What did you think
