



Home > Products > ProX Truss > Ground Support > Sleeve Blocks > Ground Support Sleeve Block for F34 Truss Segment Systems

SKU: XT-BLOCK-MK2


Permalink:

[Search on Google](#)

Ground Support Sleeve Block for F34 Truss Segment Systems

[Find A Dealer](#)

Product Images



[Download Product Images](#)

Our Products And You

Submit your
story

ProX XT-BLOCK Ground Support Sleeve Block for F34 Truss Systems

Description

The **ProX XT-BLOCK MK2** Truss Ground Support Sleeve Block is designed for F34 Series 12" Trussing and it includes 4 connecting sides and is one of the most trusted staging support systems in the industry and is built to the highest standards of safety and performance. It's a rugged and durable trussing solution perfect for live outdoor productions, nightclubs, and permanent installations. ProX XT Series Truss compares favorably to the other major trussing manufacturers. We manufacture with EN-AWT6 6082 Aluminum for safety and strength. Our XT series F34 square truss utilizes a standard conical connector system, which easily mates with other brands of the truss of the same size and connector type, and is available in a variety of lengths to suit your designs -- while our outstanding quality control and manufacturing techniques assure excellent fitment at every connection. ProX offers a wide variety of corners, base plates, connectors and accessories that add stability while expanding on limitless design configurations.

Always know your load weight for your equipment: [VERY IMPORTANT - CLICK HERE for Truss Loading Chart.](#)

- **Tolerance Free Standard Conical connector**
- **Main tube wall thickness of .08in**

XT-SQ SERIES DIMENSIONS:

- Height: 11.42in / 290mm
- Width: 11.42in / 290mm
- Weight: 21lb per 3.28 ft / 9,5kg per meter
- Main Tube: 2in / 50mm
- Wall Thickness: .08in / 2mm
- Braces: .75in / 20mm

Features

- **Manufactured in our Own Factory!**
- **Material: EN-AWT6 6082 Aluminum**
- **TUV Certified Aluminium Welding**
- **Built to exacting specifications**
- **Includes tapered shear pins with clips**



TUV is a 3rd Party Certification Body and a Nationally Recognized Testing Laboratory (NRTL). TUV provides inspections, testing, certification & training, with the ultimate objectives of reliability, safety & high quality.

ProX Truss products utilize industry-standard dimensions to be compatible to connect to/with many other manufacturers F34 trussing products.

Exterior Dimensions & Weight

18.50"H x 22.50"W x 22.50"L - Weight: 77.30 lbs

Shipping Dimensions & Weight

Box 1 of 1: 20.00"H x 24.00"W x 24.00"L - Shipping Weight: 80.00 lbs

Suggested Shipping Method: Parcel

UPC

019372406358

Our Products and You

Submit your
story

Commonly Asked Questions

+ Where can I buy one?

[submit a question](#)

Customer Testimonials

What did you think

Related Products

[Top Truss Section for Electric Motor or Manual Chain Hoist](#)

SKU: XT-TOPCM



[3.28 Ft - 1.00 M F34 Square Truss Segment | 2 mm Wall](#)

SKU: XT-SQ328





Conical Tube Ground Support Post towers Male to Male Hinge Joint Fits F31 F32 F34
SKU: XT-HINGE



Pair 1 Ton Manual Chain Hoist with 30 Ft (9 M) Chain for Stage Truss roof system and line array speakers
SKU: XT-MCH1TX2-30FT



Single 3 Ft. Outrigger Support Brace for Leveling Ground Support Truss Tower Base
SKU: XT-GSOUTS3
