



Home > Products > ProX Stands > Lighting Truss & Crankstands > XT-CRANK22FT-400 Heavy Duty 22 Ft. High Truss Crank Up Lighting Stand 400 Lbs. Capacity Includes T-Adapter Truss Mount

SKU: XT-CRANK22FT-400

Permalink: <http://www.proxdir.com/xt-crank22ft-400>

[Search on Google](#)

XT-CRANK22FT-400 Heavy Duty 22 Ft. High Truss Crank Up Lighting Stand 400 Lbs. Capacity Includes T-Adapter Truss Mount

[Find A Dealer](#)

Product Images



[Download Product Images](#)

Our Products And You

Submit your
story

ProX XT-CRANK22FT-400 Heavy Duty 22 Ft. High Truss Crank Up Lighting Stand 400 Lbs. Capacity Includes T-Adapter Truss Mount

Description

The **ProX XT-CRANKa22FT-400** is a heavy-duty crank support system that gets the job done with minimal effort. This crank stand system can support up to a 400 lb vertical load and reach a maximum height of 22'. With a base diameter of 7ft, this stand is very stable and safe.

The ProX Truss Heavy Duty Crank Stands are an integral part of the Truss SQ System for temporarily mounting lights for small to medium-sized DJ lighting at any event. It has Integrated casters, independently adjustable leg braces, and nylon guided leg sliders, which can all be used in conjunction with another same-rated stand, & trusses and T-Adapters (sold separately). Each is made with Heavy Duty All-metal components; Sturdy, steel/aluminum construction. Eliminate direct lifting and lowering of heavy loads with the ProX Truss Heavy Duty Crank Stand.

It folds easily to a portable size for transport. It's equipped with a smooth, heavy-duty cranking mechanism. Perfect for a live band and mobile DJ applications, eliminate direct lifting and lowering of heavy loads.

SAFETY INSTRUCTIONS

To avoid problems a competent person should inspect all rigging hardware, stands and equipment before each use and periodically do a major inspection for signs of wear, abuse, and general adequacy, as well as perform any manufacturer recommended preventive maintenance on schedule. Observe all warnings and usage instructions in the full manual. Use at your own risk.

Basic Usage:

1. Ensure that the stand is positioned on a hard stable surface, in a suitable location, on firm ground and clear of overhead obstacles.
2. Stabilize legs before lifting the tower or any load.
3. When outdoors, secure the tower with braces or cables, in the case of wind.
4. Check the cable, it should not show damaged or flattened areas nor broken threads.

Using the Winch:

1. For Lifting the tower, turn the winch handle clockwise.
2. For lowering the tower, turn the winch handle counter-clockwise.

Safety Notes:

1. Loading on truss and stands should comply with rated weights.
2. Lock all the safety mechanisms (safety pins, knobs)
3. Loads must be centered & balanced on each lifting unit.
4. Safety chains must be installed on each item attached to the unit.
5. Leave a safety perimeter with a radius 5ft greater than the maximum height of the stands during lifting and lowering of loads.
6. During transport, close all the sections and lock the lifting carriage.
7. Do not attempt to move the stand when loaded or in an extended position.

Service Notes:

1. Servicing and repairs must be made by qualified persons.
2. Cable, pulleys, and telescopic masts must be inspected before each use. Any damaged cable must be replaced immediately.
3. Annual inspection by an authorized technician is suggested.

Features

- **22 Ft Lighting Stand**
- **Max Vert Load: 400 lbs.**
- **Base Diameter: 83.85" / 7FT**
- **Weight: 160 lbs.**
- **Min Height: 86"**
- **Base Closed: 18.25" x 18.25"**
- **Fits: XT-TADAPTER400 (1.5 in. Diameter)**

Exterior Dimensions & Weight

73.00"H x 15.00"W x 16.00"L - Weight: 160.00 lbs

Shipping Dimensions & Weight

Box 1 of 1: 78.00"H x 20.00"W x 20.00"L - Shipping Weight: 275.00 lbs

Suggested Shipping Method: LTL

Shipping Dimensions/Weight for (2) Units
40D x 48W x 82H (LTL Shipping)
595 LBS.

UPC

022099558750

Our Products and You

Submit your
story

Commonly Asked Questions

+ Where can I buy one?

[submit a question](#)

Customer Testimonials

What did you think

Related Products



Set of (2) 17 in. Universal T-Adapter Brackets for F34/F33/F32 Triangle Square Truss Segments
SKU: XT-TADAPTER-U



6 Way Square Truss Junction Block - Includes 2 Way 8 Half Conical Couplers

SKU: XT-JB6W-2W



9.84 Ft - 3.00 M F34 Square Truss Segment | 2 mm Wall

SKU: XT-SQ984



14 Ft Heavy-duty Lighting Crank Stand for Lifting Truss 220 lbs Capacity Incl 5ft T-Bar

SKU: XT-CRANK14FT-220



18 Ft Lighting Heavy-Duty Crank Truss Stand 500 Lb. Capacity with Outriggers Center Load18'Includes T-Adapter Truss Mount

SKU: XT-CRANK18FT-500
