

ESPECIFICACIONES / ESPECIFICATIONS

Modelo / Model	FT-6860		FT-7045		FT-6033		FT-6520		FT-5323	
Altura	1980	mm	1700	mm	1700	mm	1710	mm	1710	mm
Height	77,95	ft	5,58	ft	5,58	ft	5,61	ft	5,61	ft
Máxima altura	6800	mm	7000	mm	6000	mm	6500	mm	5300	mm
Maximum height	22,31	ft	23,21	ft	16,69	ft	21,33	ft	17,39	ft
Anchura	580	mm	520	mm	520	mm	440	mm	440	mm
Width	22,3	in	20,5	in	20,5	in	17,3	in	17,3	in
Longitud	900	mm	700	mm	700	mm	600	mm	600	mm
Length	35,3	in	27,6	in	27,6	in	23,6	in	23,6	in
Anchura patas desplegadas	2170	mm	2300	mm	2300	mm	1950	mm	1950	mm
Width- stabilizers lowered	85,4	in	90,6	in	90,6	in	76,8	in	76,8	in
Longitud patas desplegadas	1830	mm	1760	mm	1760	mm	1340	mm	1340	mm
Length operating	72,1	in	69,3	in	69,3	in	52,7	in	52,7	in
Hueco base suelo	50	mm	50	mm	50	mm	50	mm	50	mm
Ground clearance	1,97	in	1,97	in	1,97	in	1,97	in	1,97	in
Brazo de carga	945	mm	650	mm	650	mm	500	mm	500	mm
Loading fork	37,20	in	25,59	in	25,59	in	19,65	in	19,65	in
Carga mínima	25	Kg	25	Kg	25	Kg	25	Kg	25	Kg
Minimum load capacity	55,12	Lb	55,12	Lb	55,12	Lb	55,12	Lb	55,12	Lb
Carga máxima máquina	600	Kg	450	Kg	330	Kg	200	Kg	235	Kg
Max. load as machine	1322,8	Lb	992,1	Lb	727,5	Lb	440,9	Lb	518,1	Lb
Carga máxima estructura	855	Kg	515	Kg	455	Kg	360	Kg	455	Kg
Max. load as structure	1885	Lb	1135	Lb	1003,1	Lb	793,6	Lb	1003,1	Lb
Peso neto	255	Kg	165	Kg	156	Kg	112	Kg	101	Kg
Net weight	562,2	Lb	363,8	Lb	343,9	Lb	246,9	Lb	222,7	Lb
Cabrestante	1200	Kg	900	Kg	900	Kg	1200	Kg	1200	Kg
Winch	2645,5	Lb	1984,2	Lb	1984,2	Lb	2645,5	Lb	2645,5	Lb
Emisiones de ruido	70	dB	70	dB	70	dB	71	dB	73	dB
Noise emissions										

Figure 101