

ESPECIFICACIONES

Modelo / Model	T100	T101	T102	T103	T104	T105	T106
Altura (mm)	2035	1290	1990	1750	1750	1770	1840
Height (ft)	6,68	4,23	6,53	330,69	330,69	5,81	6,04
Máxima altura (mm)	3800	3800	5000	5300	5300	5300	6400
Maximum height (ft)	12,47	12,47	16,4	17,39	17,39	17,39	21
Anchura (mm)	360	200	360	370	460	460	460
Width (ft)	1,18	0,66	1,18	1,21	1,51	1,51	1,51
Longitud (mm)	360	200	360	370	460	460	460
Length (ft)	1,18	0,66	1,18	1,21	1,51	1,51	1,51
Anchura patas desplegadas (mm)	1700	1570	2060	2080	2110	2110	2530
Width- stabilizers lowered (ft)	5,58	5,17	6,76	6,82	6,92	6,92	8,3
Longitud patas desplegadas (mm)	1700	1570	2060	2080	2110	2110	2530
Length operating (ft)	5,58	5,17	6,76	6,82	6,92	6,92	8,3
Hueco base suelo (mm)	0	0	0	50	50	50	50
Ground clearance (inch)	0	0	0	1,96	1,96	1,96	1,96
Carga mínima (Kg)	25	25	25	25	25	25	25
Minimum load capacity (Lb)	55,12	55,12	55,12	55,12	55,12	55,12	55,12
Carga máxima máquina (Kg)	100	100	100	150	200	225	225
Max. load as machine (Lb)	220,46	220,46	220,46	330,69	440,92	496	496
Peso neto (Kg)	23,5	24,5	31,5	41,5	69	84,5	94
Net weight (Lb)	51,81	54	69,45	91,49	152,12	186,29	207,23
Cabrestante (Kg)	350	350	350	500	500	900	900
Winch (Lb)	771,62	771,62	771,62	1102,31	1102,31	1984,16	1984,16
Emisiones de ruido (dB)	70	70	70	72	72	75	75
Noise emissions (dB)	70	70	70	72	72	75	75

Figure 66